

CONTENTS OF VOLUME 2

XIII. REPORT OF IAEA SPECIALISTS' MEETING ON INTOR-LIKE DESIGNS	1
1. Introduction	1
2. Objectives	2
2.1. Comparison of objectives	2
2.2. Discussion of objectives	2
3. Physics	13
3.1. Introduction	13
3.2. Physics design features	15
3.2.1. Fusion performance (energy multiplication rate, Q)	15
3.2.2. Burn pulse length	17
3.2.3. Impurity and particle control method	18
3.2.4. Plasma configuration	19
3.2.5. Startup assist	20
3.2.6. Operation scenario	21
3.2.7. Duty factor	22
3.2.8. Plasma heating method	23
3.2.9. Frequency of disruptions	24
3.3. Design constraints	26
3.3.1. INTOR	26
3.3.2. NET	26
3.3.3. FER	27
3.3.4. TIBER	31
3.3.5. OTR	32
3.4. Design specifications	65
4. Electromagnetics, heating and current drive technologies	65
4.1. Introduction	65
4.1.1. Load transmission with TF coils	77
4.1.2. Operating scenarios	77
4.1.3. PF coil conductors	80
5. Nuclear	81
5.1. Design specifications and parameters	81
5.1.1. Power and particle exhaust system	81
5.1.2. First wall and limiter	91
5.1.3. Blanket system	91
5.1.4. Shield system	92
5.1.5. Tritium	92
5.1.6. Test facilities	92

5.2.	Design drivers for nuclear components	93	6.2.	Design specifications	113
5.2.1.	Main design drivers for INTOR	93	6.2.1.	Summary of design specifications	113
5.2.2.	Main design drivers for NET	96	6.3.	Comparative study of main design features	122
5.2.3.	Main design drivers for FER (neutron wall loadings, fluence, tritium supply and breeding requirements)	97	6.3.1.	Introduction	122
5.2.4.	Main design drivers for TIBER	98	6.3.2.	Main design feature tabulation	122
5.2.5.	Main design drivers for OTR	99	6.3.3.	Comments on main design features	122
5.3.	Engineering design constraints	99	6.3.3.1.	Plasma configuration	122
5.3.1.	Comments on INTOR design constraints	103	6.3.3.2.	Location of PF coil system	122
5.3.1.1.	First wall	103	6.3.3.3.	Maintenance	122
5.3.1.2.	Blanket	103	6.3.3.4.	Location of vacuum boundary	122
5.3.1.3.	Shield	103	6.3.3.5.	Modularization	123
5.3.1.4.	Divertor	104	6.3.3.6.	TF coil support	123
5.3.1.5.	Tritium system	104	6.3.3.7.	Shield material	123
5.3.2.	Comments on NET design constraints	104	6.3.3.8.	Breeding requirements	123
5.3.2.1.	First wall	104	6.4.	Comparative study of design constraints	129
5.3.2.2.	Divertor	105	6.4.1.	Introduction	129
5.3.2.3.	Tritium system — local tritium inventory	106	6.4.2.	Tabulation of engineering constraints	129
5.3.3.	Comments on FER constraints	106	6.4.3.	Comments and remarks	129
5.3.3.1.	First wall	106	6.4.3.1.	Coil configuration	129
5.3.3.2.	Shield	108	6.4.3.2.	Thickness of components	129
5.3.3.3.	Divertor	108	6.4.3.3.	Gaps/voids	133
5.3.3.4.	Disruption scenario	109	6.4.3.4.	Auxiliary systems requirements	133
5.3.3.5.	Tritium system	109	6.4.3.5.	Plasma shape and size	147
5.3.4.	Comments on TIBER design constraints	110	6.4.3.6.	Component replaceability	147
5.3.4.1.	First wall	110	6.4.3.7.	Structural support system	148
5.3.4.2.	Blanket	110	6.4.3.8.	Heat transport	148
5.3.4.3.	Shield	110	6.5.	Some comparative studies of mechanical designs	148
5.3.4.4.	Divertor	110	Appendix 1	149
5.3.4.5.	Tritium system	111	Appendix 2	152
5.3.5.	Comments on OTR design constraints	111	Appendix 3	153
5.3.5.1.	First wall	111	XIV. COMPARISON OF INTOR-LIKE DESIGNS	155	
5.3.5.2.	Blanket	111	1.	Objectives	155
5.3.5.3.	Shield	111	2.	Physics constraints	156
5.3.5.4.	Divertor	111	2.1.	Confinement	157
5.3.5.5.	Tritium system	112	2.2.	Beta limit	157
6.	Mechanical and configuration	112	2.3.	Safety factor	157
6.1.	Introduction	112	2.4.	Density limit	158
6.1.1.	Specifications	112	2.5.	Plasma edge, scrape-off, fuelling	159
6.1.2.	Design features	113	2.6.	Toroidal field ripple	159
6.1.3.	Constraints	113	2.7.	Plasma heating and non-inductive current drive	159
6.1.4.	Others	113			

2.8.	Current drive methods	161	5.	Operational flexibility of OTR	207
2.9.	Design parameters	163	6.	Operational flexibility of INTOR	208
2.10.	Conclusions	164			
3.	Engineering constraints and specifications	165	XVI. SYSTEMS ANALYSIS OF INTOR-LIKE DESIGNS	213	
3.1.	Mechanical and configuration	165	1.	Introduction	213
3.2.	Electromagnetics, heating and current drive technologies	170	2.	Major features and parameters	214
3.3.	Nuclear	172	3.	Description of systems analysis codes and analysis process	216
3.3.1.	Lifetime fluence	173	3.1.	European Community systems analysis codes and analysis process	216
3.3.2.	Allowable stress for structural materials	173	3.1.1.	Introduction	216
3.3.3.	Number of lifetime cycles	173	3.1.2.	General structure of SUPERCOIL	217
3.3.4.	Disruption scenario	173	3.1.3.	Short description of component models	219
3.3.5.	First wall protection	174	3.1.4.	Plasma	219
3.3.6.	Tritium breeding requirement	174	3.1.5.	Blanket and shield	220
3.3.7.	Divertor	175	3.1.6.	TF coil system	220
3.3.8.	Alternate divertor designs for phased operations	175	3.1.6.1.	Resistive coils	220
3.3.9.	Shield requirements	175	3.1.6.2.	Superconducting coils	221
4.	Design driving features	176	3.1.6.3.	Bath cooling	221
4.1.	Ignition or finite Q	176	3.1.6.4.	Forced cooling	221
4.2.	Operation scenario and pulse length	178	3.1.7.	PF coil system and solenoid	221
4.3.	Plasma configuration and impurity control	179	3.1.8.	Geometrical modelling	222
4.4.	Startup assist	179	3.1.9.	Costing	222
4.5.	Plasma heating method	180	3.1.10.	Typical modes of running SUPERCOIL	223
4.6.	Tritium breeding capability	181	3.2.	Japan systems analysis code and analysis process	226
4.7.	Fluence target and nuclear testing	182	3.3.	USA systems analysis codes and analysis process	228
4.8.	Access for maintenance	183	3.3.1.	Introduction	228
4.9.	Conclusions	184	3.3.2.	Global constraint description	231
			3.3.2.1.	General constraints	232
XV. OPERATIONAL FLEXIBILITY OF INTOR-LIKE DESIGNS	185		3.3.2.2.	Plasma constraints	232
1.	Introduction	185	3.3.2.3.	Stress constraints	232
2.	Operational flexibility of NET	191	3.3.2.4.	Superconductor constraints	232
3.	Operational flexibility of TIBER	193	3.3.2.5.	Shielding constraints	233
3.1.	Introduction	193	3.3.3.	Module descriptions	233
3.2.	TIBER advanced steady state operation	194	3.3.3.1.	Physics	233
3.3.	TIBER pulsed inductive scenarios — ignition and LH assisted operation	195	3.3.3.2.	TF coil	233
4.	Operational flexibility of FER	201	3.3.3.3.	PF coils	234
4.1.	Introduction	201	3.3.3.4.	Shielding	234
4.2.	Plasma size flexibility	202	3.3.3.5.	Costs	234
4.3.	Plasma shape flexibility	203	3.4.	USSR systems analysis code and analysis process	234
4.4.	Flexibility of heating and current drive control	204	3.4.1.	Introduction	234
4.5.	Advanced operation scenarios	204	3.4.2.	Structure of the code complex	235

3.4.3. Functional codes	236
3.4.3.1. Codes for plasma description	236
3.4.3.2. Plasma engineering codes	237
3.4.3.3. Codes for magnet system description	237
3.4.3.4. Code for blanket/shield description	238
3.4.3.5. Code for reactor power balance description ...	238
3.4.3.6. Reactor safety related codes	238
3.4.3.7. Codes for reactor maintenance description	238
3.4.3.8. Economic model codes	238
4. Representation of INTOR-like designs	239
4.1. Comparison of physics assumptions	239
4.2. Benchmark calculation of INTOR-like design by each delegation	274
5. Sensitivity analysis	275
5.1. Design guidelines	275
5.1.1. EC design guidelines	275
5.1.2. Japan design guidelines	278
5.1.3. USA design guidelines	278
5.1.4. USSR design guidelines	280
5.2. Individual sensitivities	281
5.2.1. Purpose	281
5.2.2. Description of national studies	281
5.2.3. Discussion of results	300
5.2.4. Observations and conclusions	306
5.3. Global effects	307
5.3.1. Purpose	307
5.3.2. Description of national studies	307
5.3.3. Observations and conclusions — global effects	320
6. Relative capital cost comparisons	320
6.1. Comparison of direct capital costs	321
6.2. Major cost items	324
7. Conclusions	326
7.1. Replication	326
7.2. Individual sensitivity	326
7.3. Global effect	328
7.4. Relative costs	328
References to Chapter XVI	329