

MICROWAVE ENGINEERS' HANDBOOK

VOLUME 2

CONTENTS

DIRECTIONAL COUPLERS	1
ANTENNAS	17
FERRITES	99
DETECTION AND NOISE	121
MICROWAVE TUBES	149
SOLID STATE	159
MISCELLANEOUS	179

DIRECTIONAL COUPLERS

Multi-Aperture Directional Coupler Design	1-3
TEM Directional Couplers	3-5
TEM Directional Couplers, References	6
Ratio of End Branch Height to Center Branch Height vs. dB Coupling	7
Ratio of Center Branch Height to Main Guide Height vs. dB Coupling	7
Sidewall Directional Coupler	8
Schwinger Reversed Directional Coupler	8
Moreno Cross Guide Directional Coupler	9
Riblet Tee Slot Directional Coupler	9
Broadwall Directional Couplers	10
X-Band Waveguide Directional Coupler	11
Round Hole Cross Guide Directional Coupler	11
X-Band Sidewall Coupler	12
S-Band Sidewall Waveguide Directional Coupler	12
Coupling/Hole at 10 GHz for X-Band Half Height Waveguide	13
KU Band Waveguide Directional Coupler	13
Strip Transmission Line Directional Couplers	14-15

Cassegrain Antennas – Geometrical Relations	18	Active R and X vs. Scan Angle for $\lambda/2$ Dipoles Spaced	
Parabolic Antenna Feed Design	19	$\lambda/4$ Above Ground Plane (Dipoles Spaced 0.6	
Dish Gain vs. Aperture Diameter	20	λ Apart)	57
Gain Factor for Circular Aperture Taylor		Scanned Linear Array Beamwidth	58
Distributions	20	Beam Broadening vs. Sidelobe Level for Linear Array	59
Side Lobe Level vs. Main Beamwidth (Zero ϕ Error)	21	Direct. of Uniform Squ. Apert. vs. Scan Angle	59
Pattern Characteristics for Circular Aperture	22	Array Directivity vs. Element Spacing	60
Paraboloidal Directivity Loss Due to Random Errors	22	Subtended Angle and Path Taper of an Optical Feed	61
Aperture Gain Loss Due to Random Errors	23	Grating Lobe Position for Scanning Linear Array	61
E and H Plane Sidelobes vs. H Plane Taper	23	Directivity of Chebyshev Arrays	62
Beamwidth Conversion	24	Bandwidth of Resonant Arrays	62
Sidelobe and Gain Degradation of Blocked Aperture	24	Maximum Directivity of Chebyshev Arrays	63
Beam Deviation After Ruze	25	Directivity-Beamwidth Product to Chebyshev Arrays	64
Directivity Degradation After Silver	25	Directivity-to-Beamwidth Ratio for Chebyshev Arrays	65
Opt. Ang. Accuracy of Circ. Lobe Comparison Ant.	26	Conductance of Traveling Wave Array (25 & 30 dB	
Flyswatter Reflector Directivity	26	Sidelobe Ratio)	66
Offset Paraboloid Feed Design	27	Gain vs. Number of Elements for Broadside Scanning	
Offset Paraboloid Feed Loci	28	Chebyshev Phased Array	67
Feed Length for Spher. Refl. w/Correctg. Line Srce.	29	Maximum Element Spacing vs. Number of Elements	
BW for Spher. Refl. w/Correctg. Line Srce. Feed	30	for Desired Grating Lobe Suppression for a	
Wind Forces on Standard Antennas with Radomes	31	Phased Array	68
Wind Forces on Standard Antennas	31	Beamwidth for Scanning Chebyshev Phased Arrays	69
Far Fld. Dist. for Typ. Parabolic Ant. for Use in		Taylor Line Source with Part Equal, Part Tapered	
Computing Pwr. Density Values	32	Sidelobes	70
Power Density at $2D^2/\lambda$ for Typical Antenna	33	Norm. Direct. vs. L for Uniform and Ideal Space	
Near Field Pwr. Density Norm. to One at $2D^2/\lambda$	34	Factors	70
		Norm. Direct. vs. L for Taylor Approx. Space Factor	71

ANTENNAS

Uniform Line Srce. Pwr. Density in the Near Field	35	Sidelobe Level Degrad. from Construction Errors –	
Near Fld. Direct. Reduct. of Tapered Circ. Apert.	36	Shunt Slot Array w/Chebyshev Distr.	72
Near Fld. Direct. Reduct. of Rect. Apert. w/Separable		First Beam Position off Broadside, Uniform	
Illum.	37	Amplitude (Symmetrical and Asymmetrical Phase)	73
Minimum Spot Size of Focused Aperture	38	Pattern Build-up as f(t) in 10 Element Array	74
Taylor Line Source Beamwidth vs. Length in		Non-Uniformly Spaced Arrays	75
Wavelength	39	System Sens. vs. Ant. and Rcvr. Noise Temp.	76
Highest Sidelobe of Line Source with Center Gap	39	Total Attenuation for One-Way Transmission through	
Approx. E Field for Buried or Submerged Ant.	40	the Atmosphere	77
Normalized Distance Function for Buried Antenna	41	Galactic Noise Temperature after KO, Brown and	
Depth Attenuation for Buried Antenna	41	Hazard	78
Skin Depth in Earth or Sea at VLF & LF	42	Ant. Noise Temp. Degrad. Due to Trans. Line Loss	78
Refraction Ratio for Buried Antenna Fields	43	Radio Maps of the Sky Background (64-160 MHz)	79
Conversion of Field Strength in $\mu\text{V}/\text{M}$ to $\text{dB}/\text{KT}_0\text{B}$		Radio Maps of the Sky Background (250-910 MHz)	80
for Short Dipole	43	The Per. of an Earth Sat. in a Circ. Orbit as a Function	
Rel. Gain of Loop w/Hollow Prol. Spher. Core	44-45	of its Alt.	81
Rel. Voltage Gain of Loop w/Solid Spher. Core	46	Radio Noise Levels in Air	81
Veloc. Ratio for Max. Gain Surface Wave Ants.	47	Angle Subtended by the Earth at the Satellite as a	
Directivity and Beamwidth of Surface Wave Antennas	47	Function of Satellite Altitude	82
Opt. Rect. Horns, Giving Flare $<$ vs. L, w/Beamwidth		Satellite Coverage vs. Satellite Altitude	82
on an Aux. Scale	48	Plotting Approx. Sat. Vis. Areas Using Orth.	
Axial Mode Helical Antenna Beamwidth vs. Length	48	Meridional Proj.	83
Phase Velocity of Cigar Antenna	49	Nomograph of Path Loss as a Function of Frequency	
Transmission Through A Grid of Wires	49	and Range	84
Axial Ratio off Axis for Crossed Dipole	50	Transmission Delay Time	85
Max. Pol. Loss Between Two Ellip. Pol. Ants.	50	Nomogram, Free-Space Transmission Loss, 1000 to	
Optimally Matched Compensated Balun	51	10^6 km	86
Longitudinal Shunt Slot Parameters	52	Nomogram, Free-Space Transmission Loss for	
Edge Shunt Slot Parameters	53	Planetary Distances	87
Resonant L and Norm. R vs. F for Series Inclined Slot		Point of Reflection on Over-Water Microwave Path	88
on Waveguide Centerline	54	Quantitative Evaluation and Comparison of Elec-	
The Slot Geometry	55	trically Small Antennas	89
Displaced and Inclined (Complex) Slot Design	55	Dipole Parameters	90
Normalized Active R vs. Scan Angle for Dipoles in		Loss Factor for Copper	91
Free Space (Dipoles Spaced $\lambda/2$ Apart)	56	Air Loop Parameters	92-93
Normalized Active R vs. Scan Angle for Dipoles $\lambda/4$		Shape Factor for Cylindrical Core	94
Above a Ground Plane (Dipoles Spaced $\lambda/2$ Apart)	56	Ferrite Loop Parameters	95-96
		Quasi-Optical Apertures	97

FERRITES

Normalized External Field for Resonance as a Function of Shape for Spheroidal Samples	100	Properties of Ferrite Materials	107-108
Normalized Internal DC Field at Resonance as a Function of Shape for Spheroidal Samples	100	Demagnetizing Factors	109-110
Normalized External Field for a Very Slender Ellipsoid	101	Resonance Frequency as a Function of Applied Field and Saturation Magnetization for Different Ferrite Shapes	111
Normalized Internal Field for a Very Slender Ellipsoid	102	Resonance Frequency as a Function of Saturation Magnetization and Field for Different Demagnetizing Factors	112
Variation of Linewidth, Saturation Magnetization and Effective g-Factor with Density for an Yttrium-Iron Garnet	103	Resonance Frequency or Magnetic Field Value as a Function of N_z/N_x for $d\omega/dM = 0$	112
Variation of Linewidth, Saturation Magnetization and Effective g-Factor with Gadolinium Content in Yttrium-Gadolinium-Iron Garnet	103	Table of Thermal Conductivity and Dielectric Properties of Materials Commonly Used in Ferrite Device Design	113
Variation of Saturation Magnetization with Tem- perature for Mixed Yttrium-Gadolinium-Iron Garnet	104	Calculated Loss of 50 Ohm Gold Microstrip Lines Typically Used in Ferrite and Alumina Sub- strated Circuits	114-115
Variation of Linewidth, Saturation Magnetization and Effective g-Factor with Samarium Content in Yttrium-Samarium-Iron Garnet	105	Dielectric Transformer Design	116-117
Variation of Linewidth, Saturation Magnetization, Effective g-Factor, and Curie Temperature with an Aluminum Content in Yttrium-Aluminum- Iron Garnet	106	Nomogram for Determining Effective Junction Circulator VSWR	118
		Single Stage YIG Filter Parameters	118
		Variation of Resonance Frequency in (110) Plane for Single Stage YIG Filter with $F_0 = 5000$ MHz for pure YIG ($H_a = 43$ Oe at 23°C)	118
		Important Relationships	119

DETECTION AND NOISE

Noise Figure Measurements	122-126	Receiver R. M. S. Absolute Noise Threshold	138
Hot-Cold Noise Figure Measurements	126	Noise Figure vs. Noise Temperature	139
Noise Figure Measurement	127	SNR Degradation Due to Multiplier Noise in	
VSWR Effects in Noise Figure Measurements	128	Multiplier Chains	139
Nomograph, Correction for Second Stage Noise		Noise Power-Noise Unit Conversion Chart	140
Figure	129	Conversion of $S + N/N(\text{dB})$ to $S/N(\text{dB})$ Addition of	
Graph of Noise Correction vs. Hot Insertion Loss		Noise	141
of Gas Discharge Noise Generators	130	G/T Nomograph for 4 GHz	142
Noise Temperature Equations for Commonly Used		Instantaneous Addition of Signal and Noise in a	
Circuits	131	Dual Diversity Combiner	143
Noise Figure of Microwave Amplifiers	132	Efficiency of Non-Matched Filters Compared with	
Overall Noise Figure Nomograph	132	Matched Filter	144
Noise Generator Calibration Services Available at		Comparison of Noise Bandwidth and 3 dB Bandwidth	144
N. B. S.	133	Probability of Bit Error vs. Signal to Noise Ratio	145
Low Level Detection Characteristics	134	Flux Density Spectra of Radio Stars	146
Linear Detector, Increase of Average Output Due to		Variation of Effective Galactic and Atmospheric	
Noise	134	Noise Temperatures	146
Fluctuation of Linear Detector Output	135	Modern Low Noise Microwave Technology in 1969	148
Nomogram for Video Detector Tangential		Low Noise Transistors and Tunnel Diode Amplifiers	
Sensitivity	136	in 1969	148
Receiver Sensitivity Nomograph	137	Ultra-Low Noise TWTA's in 1969	147

MICROWAVE TUBES

Performance Characteristics of Principal Frontier Tubes 1969 State of the Art	151
Table I. Performance Characteristics of Principal Frontier Tubes	152
State of the Art — Magnetrons	153
State of the Art — Power Klystrons	154
State of the Art — Traveling-Wave Tubes	155
State of the Art — O-Type BWO's and Reflex Klystrons	156
State of the Art — Crossed Field Amplifiers and Voltage Tunable Oscillators	157

State of the Art: Avalanche (Impatt) Diode and Gunn Devices	160
State of the Art Results, Power vs. Frequency for EHF Devices	161
State of the Art: Gunn, LSA and Hybrid Devices Using Bulk GaAs	162
State of the Art: Gunn, LSA and Hybrid Devices	163
State of the Art: System Noise Figure of Broad Band Mixer Diodes vs. Frequency	164
State of the Art: Effective Input Noise Temperature of Parametric Amplifiers vs. Frequency	164
State of the Art of the Noise Measure of Impatt and Bulk GaAs Devices	165
Dynamic Range Comparison Chart for Microwave Detectors	165
State of the Art: Tunnel Diode Amplifiers and Transistors Noise Figure vs. Frequency	166
State of the Art: Semiconductor Limiting Devices, Reliable Power Handling Capability vs. Frequency	166
State of the Art: Microwave Transistors Power Source or Amplifiers	166
1971 State of the Art Laboratory Results Impatt Diodes Power vs. Frequency	167
1971 State of the Art Laboratory Results Trapatt Diodes Power vs. Frequency	167
1971 State of the Art Laboratory Results LSA Diodes Power vs. Frequency	168
1971 State of the Art Laboratory Result Transferred Electron Oscillators	168
Dissipative Effect of Power Addition for Power Amplifiers	169

SOLID STATE

Ratio of Junction Capacitance at Reverse Bias Voltage (V) to Junction Capacitance at 6 Volts Reverse Bias vs. Applied Reverse V_0	170
Electronic Constants for Typical Semiconductors	170
Nomograph for Calculation of Series Resistance of Varactor Diodes	171
Tunnel Diode Measurements	172
Tunnel Diode Figure of Merit	173
PIN Diode Circuit Design Curves	174-176
PIN Diode Power Handling Design Curves	177
X-Band — Voltage Output vs. Power Input of Point Contact Diodes	178
X-Band — Voltage Output vs. Power Input of Schottky Barrier Diodes	178

IF Amplifier Design Information	180-182
Spurious Modulation Curves	183
Dielectric Materials Chart — Properties at Micro-wave Frequencies	184-185
Skin Depth	186
Surface Roughness vs. Surface Resistance at 3000 MHz	186
Four-Place Table Decibels Return Loss to Magnitude of Voltage Reflection Coefficient	187-191
Table of First 700 Zeros of Bessel Functions	192-195
Decibels vs. Voltage and Power	196
National Bureau of Standards Calibration Services at Radio Frequencies	197-199
Characteristics of Principal Microwave Radiation Safety Standards on Exposure	200
Characteristics of Principal Microwave Oven Leakage Performance Standards	201
Velocity of Propagation for Elliptical Waveguide	202
Velocity of Propagation for Rectangular Waveguide	202
Group Delay for Elliptical Waveguide-Linear Component	203
Group Delay for Rectangular Waveguide-Linear Component	203

MISCELLANEOUS

Group Delay for Elliptical Waveguide - Parabolic Component	204
Group Delay for Rectangular Waveguide - Parabolic Component	204
Intermodulation Distortion in FDMFM Microwave Radio Relay Systems Due to Feeder Mismatch	205-206
Microwave Passive Repeater Nomograph	207
Microwave Acoustics	208-209