

CONTENTS

	<u>Page</u>
ABSTRACT	11
SUMMARY	111
I. INTRODUCTION	1
II. DESCRIPTION OF DEVELOPED MONITOR	3
III. LABORATORY EVALUATION	6
1. Evaluation of Catalytic Oxidizer	6
2. Evaluation of Permeation Distillation Device	11
3. In-Place Calibration of Integrated Monitor	17
4. Conclusions from Laboratory Evaluation	20
IV. IN-PLANT DEMONSTRATION	20
V. CONCLUSIONS	26
VI. REFERENCES	27

FIGURES

1. Continuous Tritium Monitor	4
2. Schematic Diagram of Permeation Distillation Dryer	5
3. Apparatus to Evaluate Catalytic Oxidizer	8
4. Hygrometer Response with Pt-Pd on Alumina Catalyst	9
5. Hygrometer Response with CuO on Molecular Sieve Catalyst	12
6. H ₂ O Permeability Apparatus	15
7. ⁸⁵ Kr Separation Apparatus	16
8. Configuration of Permeation Distillation Device as HT and Organic Tritium Monitor	18
9. Typical Response to Calibration Run	19
10. Monitor Response to WCF Startup	22

11.	Configuration of Permeation Distillation Device for Continuous HTO Monitor	23
12.	Response of Continuous Monitor to Change in Feed Rate	24

TABLES

I.	SAMPLING CONDITIONS AT ICPP STACK	1
II.	REQUIRED SEPARATION FACTORS	1
III.	RESULTS OF HTO PERMEABILITY TESTS	14
IV.	DAILY HTO EMISSIONS AS MEASURED BY CONTINUOUS MONITOR	25