

CONTENTS

I.	INTRODUCTION	1
II.	SUMMARY, CONCLUSIONS AND RECOMMENDATIONS	5
1.	Role of INTOR in the fusion programme	5
2.	INTOR concept	6
3.	Operation schedule for INTOR	9
4.	Alternatives	13
4.1.	Materials testing	13
4.2.	Tritium production	15
4.3.	Electricity production	16
5.	Physics and technology data bases and R and D needs	17
5.1.	Physics	18
5.2.	Magnetics and power supply	20
5.3.	Blanket and tritium	21
5.4.	Engineering	23
5.5.	Safety and environment	24
6.	Schedule and resources	25
7.	Conclusions	25
8.	Recommendations	26
III.	DATA BASE AND R AND D NEEDS ASSESSMENTS, INTOR SUGGESTED PARAMETERS AND ELECTRICITY PRODUCTION	27
1.	Introduction	27
2.	Data base assessment summaries	27
2.1.	Energy and particle confinement	27
2.2.	Impurity control, fueling and exhaust	29
2.3.	Heating	32
2.4.	Stability control	35
2.5.	Start-up, burn and shut-down control	36
2.6.	Magnetics	38
2.7.	Power supply and transfer	42
2.8.	First wall, blanket and shield	42
2.9.	Tritium	43
2.10.	Materials	45
2.11.	Systems integration and support structure	47
2.12.	Assembly and remote maintenance	49
2.13.	Shielding and personnel access	50
2.14.	Vacuum	52
2.15.	Diagnostics, data acquisition and control	53
2.16.	Safety and environment	55

3.	R and D needs assessment	57	3.4.3. Power and particle outflux to wall and limiter	106
3.1.	R and D needs assessment — energy and particle confinement	57	3.4.4. Impurity effects on heating to ignition	106
3.2.	R and D needs assessment — impurity control, fueling and exhaust	58	3.5. Burn pulse scenarios	111
3.3(a).	R and D needs assessment — heating — neutral beam	59	4. Other transport processes	112
3.3(b).	R and D needs assessment — heating — RF	60	4.1. Field ripple	112
3.4.	R and D needs assessment — stability control	61	4.1.1. General discussion and recommendations	112
3.5.	R and D needs assessment — start-up, burn and shut-down control	62	4.1.2. Effect on suprathermal ions	114
3.6.	R and D needs assessment — magnetics	63	4.2. Alpha-particle confinement	115
3.7.	R and D needs assessment — power supply and transfer	64	4.3. Synchrotron radiation	118
3.8.	R and D needs assessment — first wall, blanket and shield	65	5. R and D needs assessment	118
3.9.	R and D needs assessment — tritium	66	6. Summary	118
3.10.	R and D needs assessment — materials	67	References to Chapter IV	120
3.11.	R and D needs assessment — systems integration and support structure	68		
3.12.	R and D needs assessment — assembly and remote maintenance	68	V. IMPURITY CONTROL, FUELING AND EXHAUST	121
3.13.	R and D needs assessment — shielding and personnel access	69	1. Outline of plasma-wall interaction, impurity control, and exhaust in INTOR	121
3.14.	R and D needs assessment — vacuum	70	1.1. Burn time	121
3.15.	R and D needs assessment — diagnostics, data acquisition and control	71	1.2. Requirements for ash exhaust	121
3.16.	R and D needs assessment — safety and environment	72	1.3. Plasma contamination by impurities sorbed on the wall surface	122
4.	INTOR suggested parameters	73	1.4. Plasma contamination by first-wall materials	123
5.	Electricity production	80	1.5. Roles of a divertor	124
5.1.	Production of 10 MW _e	81	1.6. Particle and heat fluxes at the plasma boundary	124
5.2.	Production of 100 MW _e	82	1.7. Erosion of the first wall	125
5.3.	Production of net electrical power	83	2. Permissible levels of impurities	127
	IV. ENERGY AND PARTICLE CONFINEMENT	85	3. Experimental results on plasma-wall interaction	129
1.	Experimental status of confinement in tokamaks	85	3.1. Impurity production	129
1.1.	Confinement in ohmically-heated tokamaks	85	3.2. Recycling of plasma particles	131
1.1.1.	Energy confinement	85	4. Some specific means for decreasing plasma contamination	132
1.1.2.	Particle confinement	87	4.1. Wall conditioning to reduce absorbed and adsorbed impurities	132
1.1.3.	Impurity confinement	88	4.1.1. Surface treatment before assembly	132
1.2.	Confinement in tokamaks with strong auxiliary heating	90	4.1.2. Wall conditioning after assembly	132
1.2.1.	Neutral beam heating results on PLT	90	4.2. Low-Z first wall	133
1.2.2.	Neutral beam heating results on ISX-B	92	4.3. Impurity transport control	134
1.2.3.	Neutral beam heating results on T-11	93	5. Divertors for impurity control and ash exhaust	135
1.2.4.	Neutral beam heating results from other tokamaks	94	5.1. Divertor functions and exhaust requirements	135
1.3.	Recommended INTOR-relevant confinement experiments	94	5.1.1. Particle exhaust	135
1.4.	Summary — Applicability to INTOR	95	5.1.2. Energy exhaust	136
2.	Point-model studies of INTOR	96	5.1.3. Impurity control	138
2.1.	Ignition requirements on energy confinement time	96	5.1.4. Recycling of unburnt fuel from the divertor to the torus	138
2.2.	Ignition requirements on plasma beta	96	5.2. Results of divertor experiments	139
2.3.	Neutron wall loading	97	5.2.1. Poloidal divertor	139
2.4.	Heating power needed for ignition	99	5.2.2. Bundle divertor	141
3.	Computational studies of INTOR using transport codes	100	5.3. Divertor configurations for INTOR	142
3.1.	Reference transport model	100	5.3.1. Poloidal divertor	142
3.2.	Variations of the reference transport model	101	5.3.2. Bundle divertor and its improvements	145
3.3.	Particle transport	103	5.3.3. Hybrid divertor	148
3.4.	Requirements for heating to ignition	104	5.3.4. Branch (or poloidal bundle) divertor	150
3.4.1.	Beam power, energy, and pulse length needed	104	6. Non-divertor case for impurity control and ash exhaust	151
3.4.2.	Beam penetration	105	6.1. Ports for ash exhaust adjacent to toroidal limiters	152
			6.2. "Wall Lapping Plasma" with rotating resonant helical islands and mechanical valves for ash exhaust	154

6.3. Helium exhaust at a limiter consisting of a stream of small balls	154	
7. Fueling	154	
7.1. Gas puffing	155	
7.2. Pellet injection	155	
7.2.1. Current experimental programme	155	
7.2.2. Injection requirements for INTOR	156	
8. R and D needs assessment	157	
9. Summary	159	
References to Chapter V	161	
 VI. HEATING	163	
1. Introduction	163	
1.1. Objectives	163	
1.2. Possible heating methods for a tokamak reactor plasma	163	
2. Heating requirements for INTOR	165	
2.1. Power levels	165	
2.2. Pulse length	165	
2.2.1. Ignition scenario	165	
2.2.2. Driven systems	165	
2.3. Neutral-beam heating status related to INTOR	166	
2.4. Radio-frequency heating status related to INTOR	166	
3. Physics of neutral-beam injection	167	
3.1. Beam penetration	167	
3.2. Fast-ion loss channels	169	
3.2.1. Charge-exchange loss	169	
3.2.2. Orbit loss	169	
3.2.3. Ripple loss	170	
3.3. Microinstability effects	170	
3.4. Preferred injection mode for INTOR	170	
3.5. Experimental status	172	
4. Neutral-beam technology	176	
4.1. Status of neutral-beam systems	176	
4.2. Ion sources	176	
4.3. Species mix	177	
4.4. Direct energy recovery systems	177	
4.5. Efficiencies of neutral-beam systems	179	
4.6. Negative-ion beams	181	
4.7. Long-pulse beam development	182	
4.8. Deliverable power density	183	
4.9. Effects of neutron environment	184	
4.10. Beamline pumping system	186	
4.11. Gas influx from injectors	187	
4.12. Impurity influx from injectors	187	
4.13. Magnetic shielding	188	
4.14. The injector cooling system	188	
4.15. Tritium injection	189	
4.16. Availability, maintenance and reliability	189	
4.16.1. Availability	189	
4.16.2. Maintenance	189	
4.16.3. Reliability	190	
4.16.4. Redundancy	190	
4.17. Innovative power supply requirements	190	
5. Summary of research and development needs for neutral-beam heating and technology	191	
5.1. Needs prior to INTOR authorization – major development requirements	191	
5.2. Needs prior to INTOR operation	193	
6. Physics and technology of radio-frequency heating	193	
6.1. Summary assessment for RF heating in INTOR	193	
6.2. Electron cyclotron heating (ECH)	195	
6.2.1. Theoretical considerations	195	
6.2.2. Technological considerations	197	
6.2.3. ECH proposals for INTOR	197	
6.3. Lower hybrid heating (LHH)	199	
6.3.1. Physics considerations	199	
6.3.2. Technological considerations	203	
6.3.3. Lower hybrid heating proposals for INTOR	203	
6.4. Ion cyclotron range of frequencies (ICRF)	206	
6.4.1. Physics considerations	206	
6.4.2. Technological considerations	209	
6.4.3. ICRF proposals for INTOR	210	
7. Summary of research and development needs for radio-frequency heating	210	
7.1. Physics research and development needs	210	
7.2. Technology research and development needs	212	
8. Summary	215	
8.1. Summary of neutral-beam heating	215	
8.2. Summary of radio-frequency heating	216	
References to Chapter VI	217	
 VII. STABILITY CONTROL	219	
1. MHD stability limits on β	219	
1.1. Theoretical predictions	219	
1.1.1. High-n, fixed boundary modes	219	
1.1.2. Low-n modes	220	
1.1.3. Optimum profiles	222	
1.2. Experimental status	223	
1.3. Conclusions	223	
1.4. R and D needs	224	
2. Disruptions	224	
2.1. Disruptions in present-day machines	224	
2.2. Extrapolation to INTOR	226	
2.3. Conclusions	228	
2.4. R and D needs	228	
3. Equilibrium and stability control	229	
3.1. Control of position and shape	229	
3.2. Control of the scrape-off layer of a divertor	231	
3.3. Control of the current profile	231	
3.4. Induced time dependence of the wall loading	232	
3.5. Conclusions	232	
3.6. R and D needs	233	

4.	Summary	233
5.	R and D needs assessment	236
	References to Chapter VII	236
	VIII. START-UP, BURN AND SHUT-DOWN	237
1.	Start-up	237
1.1.	Build-up of the tokamak configuration	237
1.2.	Ohmic and auxiliary heating	242
1.2.1.	Current rise and ohmic heating	242
1.2.2.	Auxiliary heating and fuelling to ignition	243
1.2.3.	Problem areas	244
2.	The burn phase	247
2.1.	Duration of burn	247
2.2.	Control of burn temperature	249
2.2.1.	Field ripple	249
2.2.2.	β limits	250
2.2.3.	Compression – decompression	251
2.2.4.	Fuelling	252
2.2.5.	Subignition operation	252
2.2.6.	Other methods assessed	253
2.2.7.	Reactor relevance of burn temperature control methods	254
3.	Shut-down	255
3.1.	Initiation of shut-down	255
3.2.	Cooling and current run-down	256
4.	Non-inductive current drive	257
5.	Conclusions	257
6.	R and D needs assessment	260
7.	Summary	260
	References to Chapter VIII	263
	IX. MAGNETICS	265
1.	Introduction	265
2.	Summary	265
2.1.	Contents	265
2.2.	TF coil	265
2.3.	Induction coil	267
2.4.	Shaping and control coils	267
2.5.	Divertors	267
2.6.	R and D needs assessment	268
3.	Toroidal field system	268
3.1.	Description	268
3.2.	Trade-off considerations	268
3.2.1.	Superconducting materials	268
3.2.2.	Stabilizer material (Cu versus Al)	269
3.2.3.	Cooling mode	270
3.3.	Machine interaction	271
3.3.1.	Tolerable neutron exposure	271
3.3.2.	Pulsed poloidal field	271
3.3.3.	Toroidal field strength	271
3.3.4.	Maintenance provisions	272
3.3.5.	Disruptions	272
3.3.6.	Design guidelines	272
3.4.	Development programmes	272
4.	Induction coils	274
4.1.	Description	274
4.2.	Trade-off considerations	274
4.2.1.	Superconductor	274
4.2.2.	Operating field	274
4.2.3.	Losses	275
4.2.4.	Cooling methods	275
4.2.5.	Winding methods	275
4.2.6.	Cabling methods	275
4.2.7.	Insulation	276
4.2.8.	Structure	276
4.2.9.	Current	276
4.3.	Machine interaction	277
4.3.1.	Helium vessel and structure	277
4.3.2.	Refrigerator	277
4.3.3.	Power supplies	277
4.3.4.	Intercoil coupling	277
4.4.	Technology assessment: present and expected	278
4.5.	Development programmes	278
5.	Shaping and control coils	279
5.1.	Description	279
5.2.	Trade-off considerations	279
5.3.	Machine interactions	280
5.4.	Technology assessment	280
6.	Plasma initiation	281
7.	Technology assessment of divertors for the INTOR mission	282
7.1.	Introduction	282
7.2.	Description	282
7.3.	Trade-off considerations	284
7.4.	Machine interaction	285
7.5.	Technology assessment	285
7.5.1.	Current experimental divertors	285
7.5.2.	Current INTOR-relevant studies	286
7.5.3.	Relative feasibility of poloidal and bundle divertors for the INTOR mission	288
7.5.4.	Materials requirements	288
7.6.	Development and technology programmes	288
7.6.1.	Expectation of current divertor programmes	288
7.6.2.	Design studies needed	289
7.6.3.	Development programmes needed	289
	References to Chapter IX	289
	X. POWER SUPPLY AND TRANSFER	291
1.	Introduction	291
2.	The poloidal magnetic field system	292

2.1. All superconducting poloidal magnetic field coils outside the TF coils	292
2.1.1. Coil arrangement	292
2.1.2. System description of power supply	293
2.2. Poloidal magnetic field coils which are not all superconducting	295
2.2.1. All water-cooled copper coils	295
2.2.2. A combination of superconducting coils and water-cooled copper coils	295
2.2.3. Ohmic heating induction coil: part superconducting and part liquid nitrogen cooled	295
2.2.4. A separate plasma initiation coil	295
3. Divertor	296
3.1. Poloidal divertor	296
3.2. Bundle divertor	296
4. Toroidal magnetic field coil supply	296
5. The neutral beam injection system	297
5.1. Power system	297
5.2. Neutral beam injector protection system	298
6. Radio-frequency heating power supplies	298
7. Power for cooling	299
7.1. Machine cooling	299
7.2. Power for cryogenic refrigeration	299
7.3. Neutral beam loss cooling power	299
8. Electric power generation system	300
9. Alternative concepts	300
9.1. Superconducting energy storage system	300
9.2. High-frequency solid-state neutral beam power supplies	300
10. R and D needs assessment	301
11. Summary of power requirements and conclusions	302
References to Chapter X	304
XI. FIRST WALL, BLANKET AND SHIELD	305
1. Introduction	305
2. Summary	306
3. INTOR guiding parameters	307
4. Design choices and constraints	308
4.1. Free choices	308
4.1.1. Generation of electricity	308
4.1.2. Tritium breeding	309
4.1.3. Staged operation	310
4.2. Limited choices	310
4.3. Design constraints	311
4.4. Design examples	312
5. Reference design and alternatives	313
5.1. Reference design	314
5.2. First alternative design	314
5.3. Second alternative	315
5.4. Third alternative	315
5.5. Choice between alternatives	315
6. Blanket test facilities	315
6.1. Test channels	316
6.2. Test modules	316
6.3. Test segments	317
6.4. Other considerations	317
7. Design concepts and data base assessment for the first wall	317
8. Design concepts and data base assessment for the blanket	319
9. Data base assessment for first wall and blanket life	322
10. Design concepts and data base assessment for the shield structure	323
11. Design concepts and data base assessment for limiters, beam dumps and divertor targets	324
11.1. Limiters	324
11.2. Beam dumps	326
11.3. Divertor targets	327
12. R and D requirements	329
13. Conclusions	329
References to Chapter XI	331
XII. TRITIUM	333
1. Introduction	333
2. INTOR tritium consumption and inventory	334
3. Fuel recycle system	336
3.1. Fuel purification	342
3.2. Hydrogen isotope separation	343
3.3. Storage	346
3.4. Refueling	346
3.5. Other technologies	346
3.6. Safety	347
4. Recovery of tritium from the blanket	347
4.1. Liquid lithium	347
4.2. Lithium oxide (Li_2O)	348
4.3. Lithium aluminate (LiAlO_2)	348
4.4. Lithium orthosilicate (Li_4SiO_4) and lithium metasilicate (Li_2SiO_3)	349
4.5. Tritium removal from ceramic materials	350
4.6. Lithium alloys (LiAl , Li_7Pb_2)	350
4.7. Summary	350
5. Tritium material interaction	353
6. Analytical techniques	357
6.1. Methods used in inventory accounting	357
6.1.1. Direct methods	357
6.1.2. Inferential methods	358
6.2. Detection in liquids and breeding materials	359
6.2.1. Aqueous or organic materials	359
6.2.2. Tritium in breeding compounds	359
7. Tritium monitoring, cleanup and disposal	360
7.1. Tritium monitoring	360
7.2. Tritium containment	360
7.3. Atmosphere detritiation	362
7.4. Waste disposal	363

8. Tritium procurement, transport and safeguards	364	6.3. Electrical insulators	412
9. Conclusions	365	6.4. Stabilizer materials	412
10. R and D needs assessment	367	6.5. Irradiation effects on superconductors	417
References to Chapter XII	367	7. Irradiation effects on ceramics	419
XIII. MATERIALS	369	8. Irradiation effects on graphite	421
1. Introduction	369	8.1. Introduction	421
2. Data base assessment for unirradiated structural materials	369	8.2. Assessment	421
2.1. Alloys considered	369	8.2.1. Dimensional stability	421
2.2. Industrial base	369	8.2.2. Thermal behaviour	423
2.3. Physical properties	374	8.2.3. Mechanical behaviour	424
2.4. Fabrication	375	8.2.4. Further considerations	425
2.5. Compatibility	376	8.2.5. Chemical erosion effects	426
2.5.1. Water	377	8.3. Conclusions	427
2.5.2. Helium as a fusion reactor coolant	377	9. Data base for plasma-material interactions	427
2.5.3. Hydrogen isotope effects and compatibility	377	9.1. Classification of materials and their functional use	427
2.6. Mechanical properties	378	9.2. Neutron sputtering	428
2.7. Stress corrosion	378	9.3. Physical sputtering – ions and neutrals	428
3. Irradiation effects on structural materials	383	9.3.1. Experimental data base	428
3.1. Anticipated maximum neutron damage in INTOR	383	9.4. Blistering phenomenon	431
3.2. Swelling and mechanical properties at fusion reactor helium levels	383	9.5. Vaporization of wall materials	432
3.3. Fatigue and fatigue crack growth (FCG)	385	10. Relevant coating technology	432
3.4. Present and future data base for neutron irradiation effects on austenitic stainless steels	389	11. Overall conclusions and observations for materials data with respect to INTOR	434
3.5. Ferritic steels	392	12. R and D needs assessment	438
3.6. Titanium alloys	395	References to Chapter XIII	438
3.7. Aluminium alloys	396		
3.8. Summary of data base	397		
4. Data base for coolants	399	XIV. SYSTEMS INTEGRATION AND SUPPORT STRUCTURE	439
4.1. Water as a fusion reactor coolant	399	1. Introduction	439
4.2. Helium as a fusion reactor coolant	400	1.1. Contents	439
4.3. Summary	400	1.2. Objectives	439
5. Data base for tritium-breeding material	401	2. Design optimization considerations	440
5.1. Candidate breeding materials	401	2.1. Alternative machine topologies	440
5.2. Physical properties of Li ₂ O	401	2.2. Vacuum/atmosphere boundary	441
5.2.1. Preparation of sintered pellets	401	2.3. Reference concepts	443
5.2.2. Vapour pressure	401	2.3.1. USA suggestions	443
5.2.3. Thermal properties	402	2.3.2. European Community suggestions	445
5.3. Chemical compatibility	402	2.3.3. Japanese suggestions	447
5.3.1. Lithium compatibility	402	2.3.4. USSR suggestions	447
5.3.2. Compatibility with solid compounds	402	3. System interfaces and interactions	450
5.3.3. Reactivity with water	404	3.1. The main INTOR sizes	450
5.3.4. Compatibility of Li ₂ O with Fe-Ni-Cr alloys	404	3.2. Specification of main INTOR systems and subsystems	450
5.3.5. Compatibility of Li ₂ O with molybdenum	405	3.3. Interface chart	454
5.3.6. Compatibility with commercial-grade helium	405	4. Structure	454
5.4. Tritium release due to a diffusion process	405	4.1. System loading interactions and responses	454
6. Magnet materials	408	5. Design standards	458
6.1. Introductory remarks and summary	409	6. Test facilities and diagnostics	458
6.2. Superinsulation	409	7. Critical issues	459
	410	8. R and D requirements	460
		9. Summary	460
		References to Chapter XIV	462

XV. ASSEMBLY AND REMOTE MAINTENANCE	463
1. Introduction	463
2. Objectives	463
3. Implications of remote maintenance for INTOR	465
3.1. Remote maintenance as a requirement of machine design	465
3.2. Procedures for remote maintenance	465
3.3. Maintenance methods	466
3.4. Mock-ups for remote maintenance	466
3.5. Facilities for remote maintenance	467
3.6. Major systems recommendations	468
3.6.1. First wall (if separate from the blanket)	468
3.6.2. Blanket maintenance	469
3.6.3. Vacuum vessel	470
3.6.4. TF coils	471
3.6.5. PF coils	472
3.6.6. Shield	472
3.6.7. Vacuum system	472
3.7. Transport facilities	472
4. Failure frequency and availability assessments	473
4.1. Introduction	473
4.2. Summary of USA assessment	473
4.2.1. Approach to availability assessment	474
4.2.2. Design assumptions	475
4.2.3. Operating assumptions	476
4.2.4. Weekly maintenance activities	476
4.2.5. Quarterly maintenance activities	476
4.2.6. Bottoms-up estimate of forced outage frequencies and times	477
4.2.7. Manpower requirements	479
4.2.8. Requirements for 50% availability	479
4.2.9. Alternative operating scenario for 50% availability	481
4.3. Summary of USSR assessment	481
4.4. Impact of accidents on maintenance systems	483
5. Assembly	483
5.1. Introduction	483
5.2. Objectives of machine assembly plan	484
5.3. Facility requirements	484
5.4. Machine layouts	485
5.5. Placement tolerances and design features	485
6. Major research and development requirements	486
6.1. Development of remote handling systems	486
6.2. INTOR reactor mock-ups	486
6.3. Welding with manipulator systems	487
6.4. Viewing systems for remote welding	487
6.5. Component reliability	488
6.6. PF coil joints	488
7. Summary	488
References to Chapter XV	489
XVI. RADIATION SHIELDING AND PERSONNEL ACCESS	491
1. Introduction	491
2. Purposes of shielding	492
3. The importance of personnel access	493
4. Assessment of primary shield	494
4.1. Allowable dose at magnet	494
4.2. Composition and thickness of inboard shield	495
4.3. Composition and thickness of outboard shield	496
4.4. Radiation streaming and additional shield requirements	497
4.5. Radiation protection of other reactor components	497
5. Assessment of shielding for personnel access	499
5.1. Radiation limits and regulation	499
5.2. Limitations on the physical location and time duration for the presence of a maintenance worker	500
5.3. Maintenance procedures for reactor components, including time schedule	500
5.4. Source of radiation exposure during maintenance work after shutdown	500
6. Other implications of personnel access	500
6.1. Impact of tritium on personnel access	500
6.2. Impact of air activation (^{41}A) on personnel access	500
7. Assessment of biological shield	501
8. Nuclear data and codes for shielding design	501
9. Conclusions	503
10. R and D needs assessment	506
References to Chapter XVI	506
XVII. VACUUM	507
1. Introduction	507
2. Vacuum boundary location	508
2.1. Vacuum boundary at the first wall	508
2.2. Vacuum boundary at the back of the shield, inside the TF coils	509
2.3. Vacuum boundary at the building wall	510
2.4. Data base for large vacuum systems of today	511
2.5. Conclusions	512
3. Vacuum system (VS) of the reactor (toroidal chamber)	513
3.1. Effects of pumping different gases	513
3.2. Methods of cleaning the first wall	515
4. Vacuum requirements for plasma heating equipment	516
4.1. Neutral beam injection	516
4.2. RF heating	520
5. Superconducting magnet cryostat vacuum system	520
6. Tritium and other technological facilities vacuum system	522
7. Pumping of helium	522
8. Radiation effects on vacuum systems	524
8.1. Cryopanels	524
8.2. Seals	525
8.3. Valves	526
8.4. Other materials	526
8.5. Effects of tritium	526

9.	Remote leak detection and repair	526	2.3.5.	Japanese comments	569
9.1.	Detection of leaks	526	2.3.6.	Comments from the IAEA perspective	569
9.2.	Repair of leaks.....	527	2.3.7.	United States requirements	574
10.	Cryopump regeneration	528	2.4.	Radiation exposure of operating personnel and of the general public	575
11.	The effects of a catastrophic first wall/vacuum wall failure on the INTOR vacuum system	530	2.4.1.	United States requirements	575
12.	Leakage into the vacuum system	530	2.4.2.	European regulations	578
12.1.	Maximum permitted leak.....	530	2.4.3.	USSR requirements	580
12.2.	Probability of leaks	531	2.5.	Other hazardous materials	581
13.	Minimizing chamber evacuation time	532	2.6.	Designing for natural phenomena	581
14.	Summary	533	2.7.	Other environmental impacts	584
15.	R and D needs assessment	535	2.7.1.	The situation in the United States	584
	References to Chapter XVII	535	2.8.	Magnetic field exposures	585
			2.9.	Nonionizing radiation effects	585
			2.10.	Summary	586
	XVIII. DIAGNOSTICS, DATA ACQUISITION AND CONTROL	537	3.	Safety-related design criteria and standards	587
1.	Introduction	537	3.1.	General design criteria for nuclear plants in the United States	587
2.	Impact of general features of INTOR	538	3.2.	Quality assurance standards for fusion reactors	587
3.	Control and data processing system	539	3.3.	Criteria for protection systems	595
3.1.	General configuration	539	3.4.	Fusion-specific guides and standards	595
3.2.	Data processing	540	3.5.	Safety analyses in Japan	596
3.3.	Feedback control.....	542	4.	Accident analysis	596
3.4.	Some remarks	542	4.1.	Accident definition	596
4.	Instrumentation	543	4.2.	Tritium release	597
4.1.	Plasma diagnostics	545	4.3.	Activation product release	599
4.2.	Engineering instrumentation	547	4.4.	Fires and explosions	605
5.	Access to the tokamak torus	547	4.5.	Release of toxic materials	605
6.	Physical environment of instrumentation	551	4.6.	Electrical system accidents	607
7.	Safety system and reliability	552	4.7.	Magnet system failures	607
8.	R and D requirements	555	4.8.	Water coolant system failures	608
9.	Conclusions and recommendations	556	4.9.	Helium coolant system failures	608
	References to Chapter XVIII	558	5.	Containment requirements	608
			5.1.	Introduction	608
			5.2.	Containment under normal operating conditions	610
			5.3.	Containment under accident conditions	611
			5.4.	Explosive containment requirements	612
	XIX. SAFETY AND ENVIRONMENT	559	6.	Tritium safeguards requirements	613
1.	Introduction and summary	559	6.1.	European Community requirements	613
1.1.	General discussion of INTOR safety issues	559	6.2.	United States requirements	613
1.2.	Summary of data base assessment	561	7.	R and D needs assessment	615
2.	Safety and environmental protection regulations appropriate to INTOR	563	8.	Conclusions	616
2.1.	Licensing requirements	563	References to Chapter XIX	617	
2.1.1.	European requirements	563			
2.1.2.	United States requirements	564			
2.1.3.	USSR requirements	564			
2.2.	Release of activation products	564			
2.2.1.	European requirements	564			
2.2.2.	United States requirements	565			
2.3.	Release of tritium	565			
2.3.1.	General considerations of tritium	565			
2.3.2.	Other sources of tritium in the environment	568			
2.3.3.	Environmental behaviour of tritium	568			
2.3.4.	European requirements	569			

APPENDICES

A.1.	INTOR Workshop sessions and attendees	619
A.2.	INTOR home base organizations	620
A.2.1.	EC (Euratom) INTOR Workshop teams	620
A.2.2.	Japan INTOR Workshop teams	624
A.2.3.	USSR INTOR Workshop teams	629
A.2.4.	US INTOR Workshop teams	633

A.3. Previous tokamak reactor design parameters	638
A.4. INTOR guiding parameters	645
A.5. Supporting documentation for the INTOR Workshop	648