

TABLE OF CONTENTS

	<u>PAGE</u>
ABSTRACT	1
I. INTRODUCTION	2
II. DESCRIPTION OF THE EXPERIMENT	5
III. EXPERIMENTAL PROCEDURES	12
III.1. Rf and RG discharges in hydrogen at low pressures	12
III.1.a. The rf discharge	12
III.1.b. The RG discharge	14
i) Initiation and quenching pressures	14
ii) Influence of the rf power level	17
iii) Influence of the pressure	17
iv) Comparison of RG and simple glow discharges and effect of admixed inert gases	20
III.1.c. Cleaning of the ports and side-arms	20
III.2. Temperature of the Quadrupole By-Pass and of the connection tube	20
III.2.a. Effect of the hydrogen pressure in the QBP	23
III.2.b. Temperature of the connection tube	23
III.3. Beginning and end of a cleaning run	27
III.4. Temperature of the portholes and side-arms	30
III.5. Reoxidation and outgasing procedures	31
III.6. Measurement of parametric dependences	32
IV. FLUXES TO THE WALLS	33
IV.1. Hydrogen flux; Langmuir effect	33
IV.2. Destruction of the reaction products by the plasma of the discharge	38
IV.3. Thermal reoxidation of the wall by H <sub>2</sub> O vapour	40
V. FIRST CLEANING OF THE SURFACES	42
V.1. Time history of the apparatus	42
V.2. Arc spots	43
V.3. Impurity release from fresh surfaces	44

VI.	SURFACE DEOXIDATION BY RF AND RG DISCHARGES IN HYDROGEN	49
VI.1.	Description of a typical experiment	49
	a) Sequence of operations	49
	b) Discussion of the mass spectra - identification of the gaseous products	49
	c) Evolution of $P_{18}$ and $P_{28}$	51
VI.2.	Comparison with other cleaning runs; initial clean-down time $\tau_{cd}$	53
VI.3.	Variation with the wall temperature $T_W$	55
VI.3.	Effect of the current $I_{GD}$ of the glow discharge	55
VI.5.	Influence of the hydrogen pressure in the RG discharge on the partial pressure of water	58
VI.6.	Influence of the pump speed $S_p$	60
VI.6.a.	Experiments using the throttle valve TV 1	60
VI.6.b.	Influence of the cryopump CF	63
VI.7.	Admixed noble gases	67
VI.8.	Admixed methane	67
VI.9.	An optimized cleaning run	71
VII.	DISCUSSION OF THE RESULTS	72
VII.1.	Sputtering, arcs and carbon removal	72
VII.2	Water release	76
VII.2.a.	General remarks	76
VII.2.b.	A simplified model for the deoxidation reaction in the RG discharge	77
VII.3.	Discussion of the parametric variation of the cleaning rate $v_p$	80
	a) Variation as a function of the filling pressure $P_2$ of hydrogen	80
	b) Variation as a function of the current density $j_{GD}$	80
	c) Variation as a function of the pump speed (using the throttle valve TV 1)	81
	d) Variation produced by the cryopump CF	81
	e) Variation as a function of the wall temperature $T_W$	82
VII.4.	Water release at lower wall temperatures and in the QBP	85
VIII.	CONCLUSIONS	86
	Acknowledgements	88
	References	89

FIGURE CAPTIONS

	<u>PAGE</u>
Fig 1. Experimental apparatus	6
Fig 2. Residual gas spectrum in the QBP	8
Fig 3. Pump speeds for gases of different masses at 200 °C	9
Fig 4. Pump speed for H <sub>2</sub> as a function of pressure A: TV1 open                      B: TV1 closed	10
Fig 5a. Lowest pressures at which hydrogen plasmas can be ignited and sustained respectively, using rf power only	13
Fig 5b. Floating potential and flux density of hydrogen into the wall as a function of the rf - power; (radiofrequency discharge)	13
Fig 6a. Minimum pressure to initiate the RG discharge in H <sub>2</sub> as a function of the initially applied dc voltage for different values of the rf power	15
Fig 6b. Minimum pressure at which an RG plasma can be sustained, as a function of the initially applied voltage for different values of the rf power	15
Fig 7. Lowest pressures at which a plasma can be initiated and sustained in a simple glow discharge and in an RG discharge with 32 W of rf power	16
Fig 8. Voltage current characteristics and floating potential at $P_2 = 4 \times 10^{-3}$ for two values of the rf power	18
Fig 9. Voltage - current characteristics and floating potential for RG-discharges at $W_{rf} = 32$ Watt and various H <sub>2</sub> pressures	19
Fig 10. Voltage - current - characteristics and floating potential of RG discharge and of a pure glow discharge (at higher pressures)	21
Fig 11. Voltage - characteristics and floating potential for RG discharges with various H <sub>2</sub> -Ne mixtures	22
Fig 12. Evolution of the partial pressures of methane, water and CO after direct admission of pure H <sub>2</sub> in the RGA, $T_W = 35$ °C	24
Fig 13. Evolution of the partial pressures of methane, water and CO after direct admission of pure H <sub>2</sub> in the RGA, $T_W = 160$ °C	25
Fig 14. Variation of the H <sub>2</sub> O signal in the RGA after introduction of H <sub>2</sub> O vapour at constant inlet pressure. QBP and CT at room temperature	26
Fig 15. Variation of the characteristic time $\tau_{CT}$ for water vapour transfer across the connection tube as a function of its temperature $T_{CT}$	28

	<u>PAGE</u>
Fig 16. Variation of the water signal $U_{18}$ in the RGA after a rapid variation of $P_{18}$ in the GDV (at $t=0$ ). $T_{QBP} = 160$ °C, $T_{CT} = 180$ °C	29
Fig 17. Illustrating the procedure used to measure the variation of $P_{18}$ as function of a parameter X	32
Fig 18. Observed decrease of the $H_2$ pressure in the GDV at the start of the RG discharge: "Langmuir effect"	35
Fig 19. Flux density $\alpha\varphi_i$ of atomic hydrogen penetrating into the wall as a function of the RG - current	37
Fig 20. Rates at which $CH_4$ is destroyed by the rf and RG discharges	39
Fig 21. Rate at which $NH_3$ is destroyed by the rf and RG discharges	39
Fig 22. First clean-down of the GDV: decrease of $H_2O$ and CO partial pressures	45
Fig 23. Impurity release at the end of the first clean-down of the GDV by a RG discharge	46
Fig 24. Release of impurity gases in an RG discharge after the introduction of a new element into the GDV	48
Fig 25. Evolution of the residual gas spectra during the successive phases of an experiment	50
Fig 26. $H_2O$ and CO release from a freshly oxidized SS surface in a RG discharge	52
Fig 27. Final clean down phase of the vessel at $T_W = 200$ °C	54
Fig 28. Variation of the partial pressure $P_{18}$ of water in the RG discharge as a function of the wall temperature $T_W$	56
Fig 29. Variation of the partial pressure of water $P_{18}$ as a function of the glow discharge current	57
Fig 30. Variation of the partial pressure of water $P_{18}$ in the GDV and of the pump speed $S_p$ with the hydrogen pressure $P_2$ in the RG discharge	59
Fig 31. "Gedankenexperiment" illustrating measurements with the throttle valve TV1	60
Fig 32. Expected variations of the hydrogen concentrations $n_2$ in B and $v_2$ in M	61
Fig 33. Expected variation of the water concentration $v_{18}$ in M and of the total concentration $n \approx n_2$ in B	62
Fig 34. Influence of the roughing speed on the elimination rate of water	64
Fig 35. Effect of the $LN_2$ cryopump on the elimination rate of water	65

	<u>PAGE</u>
Fig 36. Effect of the $LN_2$ cryopump on the elimination rate of water at the end of the cleaning run illustrated on fig. 26.	66
Fig 37. Cracking of $CH_4$ in a RG discharge and corresponding appearance of CO with walls at room temperature 1 % $CH_4$ + 99 % $H_2$	68
Fig 38. Cracking of $CH_4$ in a RG discharge and corresponding appearance of CO with oxidized walls at room temperature: 2,5 % $CH_4$ + 97,5 % $H_2$	69
Fig 39. The beginning of an "optimized" cleaning run	73
Fig 40. Variation of $n_{18}$ as a function of $I_{GD}$ : a) without $LN_2$ in the cryopump, b) with $LN_2$ in the cryopump CF	83