

Contents

| | |
|--|----|
| <i>1 Introduction</i> | 1 |
| 1.1 Review of Part I | 1 |
| 1.2 Topical Outline | 2 |
| 1.3 Organization of the Book | 5 |
| <i>References</i> | 6 |
| | |
| <i>2 Optimum Demodulators</i> | 7 |
| 2.1 Model of an Angle-Modulation System | 7 |
| 2.2 An Intuitive Approach to Demodulator Design | 9 |
| 2.3 Maximum A-Posterior Estimates | 15 |
| 2.4 Optimum Demodulator Structures | 16 |
| 2.5 System Design and Performance | 24 |
| 2.5.1 Derivation of the Unrealizable Mean-Square Error | 24 |
| 2.5.2 Filter Design | 26 |
| 2.6 Practical Considerations | 28 |
| 2.6.1 Oscillator Model | 28 |
| 2.6.2 Post-loop Filtering | 29 |
| 2.6.3 Loop Noise Bandwidth | 30 |
| 2.6.4 External VCO Control | 31 |
| 2.7 Summary | 31 |
| 2.8 Problems | 33 |
| <i>References</i> | 35 |

| | | | | | |
|----------|---|------------|--|--|--|
| 3 | <i>Phase Estimation: The Synchronization Problem</i> | 37 | | | |
| 3.1 | Oscillator Instability Analysis | 39 | | | |
| 3.2 | Nonlinear Analysis in the Absence of Noise | 41 | | | |
| 3.2.1 | First-Order Loop: Constant-Frequency Offset | 43 | | | |
| 3.2.2 | Second-Order Loop: Constant-Frequency Offset | 47 | | | |
| 3.2.3 | Second-Order Loop: Constant Acceleration | 51 | | | |
| 3.3 | Nonlinear Analysis in the Presence of Noise | 54 | | | |
| 3.3.1 | Fokker-Planck Techniques | 55 | | | |
| 3.3.2 | Perturbation and Approximation Techniques | 62 | | | |
| 3.4 | Related Topics | 62 | | | |
| 3.4.1 | Optimum Tracking Systems: Time-varying | 63 | | | |
| 3.4.2 | Optimum Tracking Systems: Time-invariant | 65 | | | |
| 3.4.3 | Minimum Acquisition Time Systems | 68 | | | |
| 3.4.4 | Phase Detector Design | 68 | | | |
| 3.4.5 | Noisy Acquisition | 69 | | | |
| 3.4.6 | Bandpass Limiters before the Loop | 70 | | | |
| 3.5 | Summary: Synchronization Problems | 70 | | | |
| 3.6 | Problems | 71 | | | |
| | <i>References</i> | 82 | | | |
| 4 | <i>Frequency Modulation</i> | 85 | | | |
| 4.1 | Model for Frequency-Modulation System | 85 | | | |
| 4.2 | Optimum FM Demodulators: Threshold Constraint | 91 | | | |
| 4.2.1 | Conventional Wiener Approach | 92 | | | |
| 4.2.2 | Simplified Wiener Approach | 93 | | | |
| 4.2.3 | State-variable Approach | 93 | | | |
| 4.2.4 | Examples of FM System Design | 94 | | | |
| 4.3 | Optimum FM Demodulators: Bandwidth Constraint | 100 | | | |
| 4.4 | Summary | 104 | | | |
| 4.4.1 | FM System Design Summary | 104 | | | |
| 4.4.2 | Phase-modulation Systems | 105 | | | |
| 4.4.3 | Comparison of AM, FM, and PM Systems | 108 | | | |
| 4.5 | Problems | 110 | | | |
| | <i>References</i> | 116 | | | |
| 5 | <i>Optimum Angle-Modulation Systems</i> | 118 | | | |
| 5.1 | Optimum Pre-emphasis Filters: Threshold Constraint | 120 | | | |
| 5.2 | Optimum Pre-emphasis Filters: Bandwidth Constraint | 126 | | | |
| 5.3 | Suboptimum Pre-emphasis Filters | 130 | | | |
| 5.3.1 | Design of Suboptimum Systems | 131 | | | |
| 5.3.2 | Summary | 134 | | | |
| 5.4 | Bounds on the Performance of Analog Message-Transmission Systems | 134 | | | |
| 5.4.1 | Rate-distortion Bound | 136 | | | |
| 5.4.2 | Performance Comparison: Infinite-bandwidth Channel | 149 | | | |
| 5.4.3 | Performance Comparison: Bandwidth Constraint | 152 | | | |
| 5.4.4 | Summary | 155 | | | |
| 5.5 | Conventional Discriminators | 156 | | | |
| 5.5.1 | Weak Noise Analysis | 157 | | | |
| 5.5.2 | Threshold Behavior | 161 | | | |
| 5.6 | Summary | 164 | | | |
| 5.7 | Problems | 167 | | | |
| | <i>References</i> | 173 | | | |
| 6 | <i>Comparison of Transmission Systems</i> | 175 | | | |
| 6.1 | Sampled and Quantized Systems | 176 | | | |
| 6.2 | Quantizer Analysis | 180 | | | |
| 6.3 | Binary Uncoded Systems | 185 | | | |
| 6.4 | Orthogonal Signals | 190 | | | |
| 6.5 | Coded Digital Systems | 193 | | | |
| 6.6 | Summary | 197 | | | |
| 6.7 | Problems | 199 | | | |
| | <i>References</i> | 202 | | | |
| 7 | <i>Nonlinear Estimation Theory: Alternative Approaches</i> | 204 | | | |
| 7.1 | Differential-Equation Approach to MAP Estimation | 205 | | | |
| 7.1.1 | MAP Interval Estimation | 206 | | | |
| 7.1.2 | Realizable MAP Point Estimation and Invariant Imbedding | 209 | | | |
| 7.2 | Markov Process Approach | 216 | | | |
| 7.3 | Summary | 222 | | | |
| 7.4 | Problems | 224 | | | |
| | <i>References</i> | 228 | | | |

| | | |
|----------|---|------------|
| 8 | <i>Analog Communication over Randomly Time-varying Channels</i> | 230 |
| 8.1 | Model and Possible Approaches | 230 |
| 8.1.1 | Model | 230 |
| 8.1.2 | Possible Approaches | 232 |
| 8.2 | Derivation of the Optimum Receiver: Rayleigh Channels | 236 |
| 8.2.1 | MAP Equations: Memoryless Rayleigh Channel | 237 |
| 8.2.2 | Angle Modulation: Rayleigh Channel | 240 |
| 8.2.3 | Joint Estimation of Message and Channel Processes | 242 |
| 8.2.4 | Realizable MAP and MMSE Estimators | 244 |
| 8.3 | Performance Bounds and Approximations | 249 |
| 8.3.1 | Mean-square Error Bound | 249 |
| 8.3.2 | Perfect-measurement Bound | 252 |
| 8.3.3 | Receiver Design and Performance in Slowly Fluctuating Channels: Quasi-Stationary Analysis | 253 |
| 8.4 | Summary | 260 |
| 8.5 | Problems | 261 |
| | <i>References</i> | 264 |
| 9 | <i>Discussion</i> | 265 |
| 9.1 | Related Topics | 265 |
| 9.1.1 | Multiplex Systems | 265 |
| 9.1.2 | Diversity Systems | 271 |
| 9.1.3 | Synchronization and Tracking Systems | 274 |
| 9.2 | Summary of Part II | 275 |
| 9.3 | Preview of Part III and <i>Array Processing</i> | 278 |
| 9.4 | Problems | 280 |
| | <i>References</i> | 284 |
| | <i>Appendix: State Variable Analysis Procedures</i> | 286 |
| | <i>Glossary</i> | 329 |
| | <i>Author Index</i> | 343 |
| | <i>Subject Index</i> | 347 |